

VeriLynx Full-Frame Video Camera

Under World Athletics Technical Rule 30.1.1, horizontal jump take-off failures are re-defined to include any breaking of the vertical plane of the take-off line. Rule 29.5 strongly encourages judges to use video or other technology to assist the decision process. **VeriLynx Field Event Verification cameras**, along with special configuration of the FinishLynx software, can be used for this purpose.

The VeriLynx camera is an Ethernet-based, full-frame digital video camera that integrates with the FinishLynx software produce time-stamped videos. FinishLynx software version 12.00 and later includes the VeriLynx profile. This profile is customized to support the use of VeriLynx cameras for video review of field events, such as the verification of take-off fouls in the Long or Triple Jump events.



Align the VeriLynx camera with the take-off board, load the field event start list, capture, verify, and timestamp every attempt. VeriLynx will save all images to disk in real-time (no image loss) and allow you to quickly review every attempt for every athlete, providing proof in case of a foul.

The VeriLynx camera captures up to **1280 x 720** pixels at **30 fps**. The camera includes a P-Iris motorized lens so the zoom and focus can be adjusted remotely within the FinishLynx software. It also has a sturdy plastic housing that protects the lens and rear connections from moisture and damage. Set up the VeriLynx camera at your next field event and start capturing high-definition, time-stamped videos to verify each attempt.

Field Event Verification Has Never Been Easier

Camera	Rate	Height	Mode	Gain	Orientalio
Long Jump Women					
Attempts					
Camera 1	30	1680	Zoom 100%	254 (60)	Left
Camera 2	5	720	Zoom 100%	192 (60)	Left

#	ToId	First Name	Last Name	Affiliation
0	671	Stacey	Bell	Missouri
0	677	Lauren	Kalnas	Monmouth
0	624	Maria	Allen	Iowa
0	522	Nora	Wood	ASU - Arizona
0	613	Brenda	Olsen	Idaho
0	551	Theresa	Roberts	BYU

VeriLynx Video integrated with the FinishLynx Software

VeriLynx Camera Hardware Specifications

Shutter Speed	Automatic
JPEG image quality	Up to 5 megapixels
Gain	Automatic
Lens	2.8-8.5mm, f/1.2, Motorized Zoom Lens
Power Supply	Power-Over-Ethernet (PoE 802.3af); 12VDC; 24 VAC
Dimensions	5.07" (L) x 2.72" (W) x 2.76"(H)
Weight	0.4 lb (0.165 kg)
Construction	Plastic and aluminum

Integration with FinishLynx Timing Software

- Remotely adjust the camera's Zoom and Focus within the FinishLynx software to optimize image quality
- VeriLynx videos can be advanced and rewind frame-by-frame to ensure judges can find the frames showing the athletes' attempts. Videos can also be reviewed in real time while the event is still underway.
- FinishLynx enables the standard EtherLynx camera features to be used with VeriLynx cameras, including zoom, automatic scrolling, gamma, brightness, and contrast adjustment.
- VeriLynx video images are stored on the computer as individual images and can be printed directly from the FinishLynx software
- VeriLynx videos can be manually cropped, viewed in forward or reverse, viewed at different speeds, exported to AVI format, and uploaded to the internet if desired.
- VeriLynx video can be exported to .avi and uploaded to YouTube, Facebook, or other popular services
- Pre-configured profile available with standard FinishLynx installation giving a customized user interface for field events
- Ability to load field events from the field event schedule file (fldlynx.sch)
- Ability to view a vertical line in alignment mode for VeriLynx cameras to facilitate camera alignment with the take-off board
- Ability to automatically capture based on detected motion and review all attempts from a flight into the same FinishLynx image
- Ability to set the ACM active area so it is limited to the image's vertical area of the take-off board
- Ability to mark/log attempts with the time of day to allow quick review of all attempts for each athlete during or after the event
- Ability to display the attempt number of each attempt in the Results Zone and on the image using Line Labels
- Ability to automatically export an image (jpg) when an attempt is marked/logged
- Ability to time track (scrolling through an image of one camera refreshes the other image panes with the equivalent frame) between images of multiple cameras to easily review different angles, including the option of using a front-facing camera to identify the athlete